

Tattoo RW is an Evolis printer for singlesided rewritable cards.

> It effortlessly matches all your expectations when it comes to flexibility, affordability, sustainable development, and regular data updates.

THE PRINTER FOR REWRITABLE CARDS

Tattoo RW is the ultimate solution for your temporary badges and cards that require regular updates.

It is the ideal solution to revise and reprint within seconds:

- visitor's details on an access control badge,
- transit passes,
- passes for ski and holiday resorts,
- student IDs,
- membership cards with subscription details.
- loyalty cards with the updated number of points, as well as applicable special offers.

With Tattoo RW, your cards are updated whenever required, while a same card can be erased, revised and printed anew up to 500 times.

FLEXIBILITY

You can deliver a new card anytime it is required! The erase/write cycle is extremely fast and you can erase, encode, and reprint new data in a matter of seconds.

A COST-EFFICIENT SOLUTION

This revolutionary rewritable technology requires no ribbon, which translates into valuable savings.

No need to throw away your cards each time you need an update: erase and reprint only updated data on your existing card!

ENVIRONMENTAL-FRIENDLY

Tattoo RW adheres to sustainable development. It uses rewritable cards and requires no ribbon: Tattoo RW helps you reduce your environmental footprint.

DATA UPDATES


Now with Tattoo RW, data encoded on magnetic stripes or on contactless chips can also be displayed and updated on the card surface.

For example, loyalty points can be printed on a card and updated at each checkout.



REWRITABLE CARD HOW DOES IT WORK?

Tattoo RW is a ribbon-free printer that uses rewritable cards. Such cards contain a thermochromatic material that turns visible, or vanishes, according to the applied temperature. This reversible process makes it possible to erase and print on the same card up to 500 times. Your card turns into a powerful medium that displays temporary or updatable data such as bonus points and special offers on a loyalty card, or the name and relevant details of visitors on a corporate badge.



SPECIFICATIONS

- 300 dpi print head for premium quality printing (11.8 dots/mm)
- USB & Ethernet connections
- 16 MB RAM
- Detachable feeder with a capacity of 100 cards (0.76 mm or 30 mil)
- Detachable output hopper with a capacity of 15 cards (0.76 mm or 30 mil)
- 1-Button and 4-LED control panel
- White body, brilliant blue cover

ENCODING OPTIONS

- HiCo/LoCo Magnetic stripe encoder ISO 7811 or JIS2
- Contactless encoder ISO14443A & B, Mifare, DesFire (USB connection)

- Direct thermal printing and erasing on rewritable material
- Maximum print area: 48 mm x 76 mm (1.89" x 2.99")

ERASING & PRINTING SPEED

- 8 seconds (manual)
- 12 seconds (card feeder)
- 3-Track ISO magnetic encoding: 4 seconds per card

- Manual card insertion and delivery
- Card-feeder insertion and delivery to removable hopper
- Automated Mode: selects a card from the feeder if no card is inserted manually

CARD FORMAT

■ CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 2.125" x 3.37")

- Rewritable thermochromic material
 - Mitsubishi Black & Blue
 - Ricoh upon request
 - Other material upon request and validation

CARD THICKNESS

■ From 0.5 mm to 0.76 mm (20 to 30 mil)

SUPPORTED PLATFORMS

Windows® · XP Vista 32/64 W7 32/64

INTERFACE

■ USB & Ethernet (USB cable supplied)

PRINTER FORM FACTOR

- Without output hopper 166 mm (6.54") (H) x 290 mm (11.42") (L) x 187 mm (7.36") (W)
- With output hopper: 166 mm (6.54") (H) x 368 mm (14.49") (L) x 187 mm (7.36") (W)

PRINTER WEIGHT

■ 2.4 Kg (5.3 lbs)

POWER SUPPLY

- Power supply: 100/240 V AC, 1.8 A, 50-60 Hz
- Printer: 24 V DC. 3 A

ENVIRONMENTAL CONDITIONS

- Min/Max operating temperature: 15°/30°C (59°/86° F)
- Humidity: 20% to 65% non-condensing
- Min/Max storage temperature: -5°/+70°C (23°/158° F)
- Storage humidity: 20% to 70% non-condensing ■ Operating ventilation: free air

WARRANTY

- 2 years (printer and print head), limited to 15,000 inserted cards¹
- 1 Warranty Subject to observance of specific conditions and use of Evolis High Trust® consumables

EUROPE - MIDDLE-EAST - AFRICA

Evolis Card Printer - 14 avenue de la Fontaine - ZI Angers-Beaucouzé 49070 Beaucouzé - France

T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

AMERICAS - Evolis Inc. - Fort Lauderdale - evolisinc@evolis.com

ASIA-PACIFIC - Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

INDIA - Evolis India - Mumbai - evolisindia@evolis.com CHINA - Evolis China - Shanghai - evolischina@evolis.com

www.evolis.com

⊠K40CERa

Printhead

